Printing date: 04.11.2026
Revision date: 04.11.2026
Version no. 13

Safety data sheet
according to UK REACH

*
SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**
· **Trade name: ULTRAFILL EPOXY FILLER Part A**

· Article number: V679
· UFI: 92V1-D0UR-Y006-05P9
· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
· Sector of Use
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
· Product category PC9b Fillers, putties, plasters, modelling clay
· Process category PROC0 Other
· Environmental release category ERC3 Formulation into solid matrix
· Article category AC7 Metal articles
· Technical function Corrosion inhibitor
· Application of the substance / the mixture Surface protection
· **1.3 Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**

VEMAR YACHT COATINGS
HB BODY S.A. ATHENS - DIYLISTIRION AV. - GR 19300 - ASPROPYRGOS - GREECE
T: +30 210 55 90 411-2 F: +30 210 55 90 713
email: sales@vemarcoatings.com website: www.vemarcoatings.com

· **Further information obtainable from:**

VEMAR YACHT COATINGS
HB BODY S.A. ATHENS - DIYLISTIRION AV. - GR 19300 - ASPROPYRGOS - GREECE
T: +30 210 55 90 411-2 F: +30 210 55 90 713
email: sales@vemarcoatings.com website: www.vemarcoatings.com

· **1.4 Emergency telephone number:**
Regional Medicines and Poisons Information Centre NI
Pharmacy Department, Royal Hospital Suite
Grosvenor Road Belfast
Telephone: +44 28 90 63 2032
Fax: +44 28 90 24 80 30
Emergency telephone: 844 892 0111
E-mail address: nirdic.nirdic@belfasttrust.hscni.net
Members of the public seeking specific information on poisons should contact:
In England and Wales: NHS 111 - dial 111
In Scotland: NHS 24 - dial 111

*
SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**
· **Classification according to Regulation (EC) No 1272/2008**


GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.


GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

· **Additional information:** The full text of the classification and labelling elements mentioned is given in Section 16.

Continue on page 2

Printing date: 04.11.2026
Revision date: 04.11.2026
Version no. 13

Trade name: ULTRAFILL EPOXY FILLER Part A

(Contd. of page 1)

· **2.2 Label elements**
· **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
· Hazard pictograms



GHS07 GHS09

· Signal word Warning
· Hazard-determining components of labelling:
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs
· Hazard statements
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
· Precautionary statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves / eye protection / face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**
After use, clean all equipment with the recommended solvent. Collect all solvent waste and residues for disposal as hazardous waste. Do not pour solvent or paint residues down the drain or into the environment.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
· **2.3 Other hazards**
· **Results of PBT and vPvB assessment**
This product contains no substance that is considered to be persistent,bioaccumulating or non toxic(PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
· PBT: Not applicable
· vPvB: Not applicable

*
SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**
· **Description:** Mixture of hazardous substances listed below with nonhazardous additions.
· **Dangerous components:**

CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	≥50-<60%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4	oxirane, mono[(C12-14-alkyloxy)methyl] derivs Skin Irrit. 2, H315; Skin Sens. 1, H317	≥5-<15%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2	titanium dioxide Carc. 2, H351 Note: V, W, 10	1-<5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

*
SECTION 4: First aid measures

· **4.1 Description of first aid measures**
· **General information:** Immediately remove any clothing soiled by the product.
· **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contanct lenses in case of eye contamination and irrigae copiously with clean water for at least 15 minutes trying to hold the eye lids open.
· **After swallowing:** If symptoms persist consult doctor.
· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

Continue on page 3

Trade name: ULTRAFILL EPOXY FILLER Part A

(Contd. of page 2)

· **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
· **5.3 Advice for firefighters**
Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products
· **5.6 Fire and explosion Hazards**
· **Speial protective equipment and fire fighting procedures:**
Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.
· **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

*

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures** Not required
· **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
· **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
· **Information about fire - and explosion protection:** No special measures required.
· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
· Information about storage in one common storage facility: Not required
· Further information about storage conditions: Keep container tightly sealed.
· **7.3 Specific end use(s)** No further relevant information available.

*

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**
· **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists valid during the making were used as basis.
· **8.2 Exposure controls**
· **Personal protective equipment:**
· General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
· Respiratory protection:
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
· Protection of hands:



Protective gloves

Continue on page 4

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.
· Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
· For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:
The breakthough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the baseis of the different substances in the preparation.
· For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Rubber gloves
· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

*

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**
· **General Information**

· Appearance:	
Form:	Pasty
Colour:	White
· Odour:	Characteristic
· Odour threshold:	Not determined
· **pH-value:**	Mixture is non-soluble (in water).
· **Change in condition**	
Melting point/freezing point:	Undetermined
Initial boiling point and boiling range:	Undetermined
· **Flash point:**	249 °C
· **Flammability**	Not applicable
· **Autoignition temperature:**	N/A
· Decomposition temperature:	Not determined
· **Ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Product does not present an explosion hazard. Risk of explosion by shock, friction, fire or other sources of ignition.
· **Explosion limits:**	
Lower:	Not determined
Upper:	Not determined
· **Vapour pressure:**	Not determined
· **Density at 20 °C:**	0.83 g/cm³
· Relative density	Not determined
· Vapour density	Not determined
· Evaporation rate	Not determined
· **Solubility in / Miscibility with**	
water:	Not miscible or difficult to mix.
· **Partition coefficient: n-octanol/water:**	Not determined
· **Viscosity:**	
Dynamic at 20 °C:	3,145 mPas
Kinematic:	Not determined
· **Solvent content:**	
Organic solvents:	≥0.1-<0.2 %
VOC (EC)	≥1-<1.5 g/l
Solids content (volume):	99.9 %

Continue on page 5

Trade name: ULTRAFILL EPOXY FILLER Part A

(Contd. of page 4)

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** No dangerous reactions known.
· **10.4 Conditions to avoid** No further relevant information available.
· **10.5 Incompatible materials:** No further relevant information available.
· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

*

SECTION 11: Toxicological information

· **11.1 Information on toxicological effects**
· **Acute toxicity** Based on available data, the classification criteria are not met.
· LD/LC50 values relevant for classification:

13463-67-7 titanium dioxide

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

· Primary irritant effect:
· Skin corrosion/irritation
Causes skin irritation.
· Serious eye damage/irritation
Causes serious eye irritation.
· Respiratory or skin sensitisation
May cause an allergic skin reaction.
· **Additional toxicological information:**
· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
· Germ cell mutagenicity Based on available data, the classification criteria are not met.
· Carcinogenicity Based on available data, the classification criteria are not met.
· Reproductive toxicity Based on available data, the classification criteria are not met.
· STOT-single exposure Based on available data, the classification criteria are not met.
· STOT-repeated exposure Based on available data, the classification criteria are not met.
· Aspiration hazard Based on available data, the classification criteria are not met.

*

SECTION 12: Ecological information

· **12.2 Persistence and degradability**
This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **Ecotoxical effects:**
· Remark: Toxic for fish
· **Additional ecological information:**
· General notes:
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** This product contains no substance that is considered to be persistent,bioaccumulating or non toxic(PBT).
· **vPvB:** Not applicable
· **12.6 Other adverse effects** No further relevant information available.

*

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
· **European waste catalogue**

HP4	Irritant - skin irritation and eye damage
HP7	Carcinogenic
HP13	Sensitising
HP14	Ecotoxic

Continue on page 6

Trade name: ULTRAFILL EPOXY FILLER Part A

(Contd. of page 5)

· **Uncleaned packaging:**
· Recommendation: Disposal must be made according to official regulations.

*
SECTION 14: Transport information

· **14.1 UN-Number**
· **ADR, IMDG, IATA** UN3082

· **14.2 UN proper shipping name**
· **ADR** UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))
· **IMDG** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), PENTANES), MARINE POLLUTANT
· **IATA** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))

· **14.3 Transport hazard class(es)**
· **ADR**



· Class 9 (M6) Miscellaneous dangerous substances and articles.
· Label 9
· **IMDG, IATA**



· Class 9 Miscellaneous dangerous substances and articles.
· Label 9

· **14.4 Packing group**
· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:** Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
· **Marine pollutant:** Symbol (fish and tree)
· **Special marking (ADR):** Symbol (fish and tree)
· **Special marking (IATA):** Symbol (fish and tree)

· **14.6 Special precautions for user** Warning: Miscellaneous dangerous substances and articles.
· Hazard identification number (Kemler code): 90
· EMS Number: F-A,S-F
· Stowage Category A

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable

· **Transport/Additional information:**
· ADR
· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
· Transport category 3
· Tunnel restriction code (-)
· IMDG
· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

Continue on page 7

Trade name: ULTRAFILL EPOXY FILLER Part A

(Contd. of page 6)

· **UN "Model Regulation":** UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700)), 9, III

*
SECTION 15: Regulatory information

•3Z

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS07 GHS09

· Signal word Warning

· Hazard-determining components of labelling:
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs

· Hazard statements
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves / eye protection / face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category E2 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 78

· Additional information on Entry 78
The estimated overall proportion of microplastics in the mixture is approx. 0.5-1 %
Process the product in closed systems or with suitable extraction/filtering techniques avoid release to soil wastewater surface water
Preferably clean equipment surfaces mechanically after use e g cloths collect residues as solid waste
Collect cleaning waters separately and forward them to appropriate disposal do not discharge into the sewer system
Collect product residues and contaminated packaging in closed containers do not rinse dispose of in accordance with legal requirements

· Synthetic polymer microparticles

Acrylic Polymer 0.5-1%

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Continue on page 8

Trade name: ULTRAFILL EPOXY FILLER Part A

(Contd. of page 7)

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS
None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors
None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors
None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

*
SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.
H411 Toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Contact:**

VEMAR YACHT COATINGS
HB BODY S.A. ATHENS - DIYLISTIRION AV. - GR 19300 - ASPROPYRGOS - GREECE
T: +30 210 55 90 411-2 F: +30 210 55 90 713
email: sales@vemarcoatings.com website: www.vemarcoatings.com

· *** Data compared to the previous version altered.**

Continue on page 9

Trade name: ULTRAFILL EPOXY FILLER Part A

(Contd. of page 8)

*
Annex: Exposure scenario

· **Short title of the exposure scenario**
· **Sector of Use**
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
· **Product category** PC9b Fillers, putties, plasters, modelling clay
· **Process category** PROC0 Other
· **Article category** AC7 Metal articles
· **Environmental release category** ERC3 Formulation into solid matrix
· **Technical function** Corrosion inhibitor
· **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
· **Conditions of use** According to directions for use.
· **Duration and frequency** Frequency of use:
· **Physical parameters**
The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.
· **Physical state** Fluid
· **Concentration of the substance in the mixture** The substance is main component.
· **Used amount per time or activity** Smaller than 100 g per application.
· **Other operational conditions**
· **Other operational conditions affecting environmental exposure** Use only on hard ground.
· **Other operational conditions affecting worker exposure**
Avoid contact with eyes.
Avoid contact with the skin.
Avoid long-term or repeated skin contact.
· **Other operational conditions affecting consumer exposure** No special measures required.
· **Other operational conditions affecting consumer exposure during the use of the product** Not applicable
· **Risk management measures**
· **Worker protection**
· Organisational protective measures
Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.
· Technical protective measures
Use product only in enclosed systems.
Ensure that suitable extractors are available on processing machines
· Personal protective measures
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes.
Tightly sealed goggles
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Measures for consumer protection**
Ensure adequate labelling.
Observe consumer information and advice on safe use.
· **Environmental protection measures**
· Water
Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.
Do not allow to reach sewage system.
· Soil
Prevent contamination of soil.
The product is only processed over the concrete collecting basin.
· **Disposal measures** Ensure that waste is collected and contained.
· **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
· **Waste type** Partially emptied and uncleaned packaging
· **Exposure estimation**
· **Consumer**
Not relevant for this Exposure Scenario.
This product is to be used by professional technicians only.
· **Guidance for downstream users**
Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.