

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **VEMAR COMFORT ANTIFOULING**

Article number: V652
UFI: DS01-H0N9-700R-KQCJ

1.2 Relevant identified uses of the substance or mixture and uses advised against

Life cycle stages PW Widespread use by professional workers
Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Product category PC8 Biocidal products
Process category PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
Environmental release category ERC12c Use of articles at industrial sites with low release
Article category AC30 Other articles with intended release of substances
Technical function Biocide
Application of the substance / the mixture Surface protection

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:



VEMAR YACHT COATINGS
HB BODY S.A. ATHENS - DIYLSTIRION AV. - GR 19300 - ASPROPYRGOS - GREECE
T: +30 210 55 90 411-2 F: +30 210 55 90 713
email: sales@vemarcoatings.com website: www.vemarcoatings.com

Further information obtainable from:



VEMAR YACHT COATINGS
HB BODY S.A. ATHENS - DIYLSTIRION AV. - GR 19300 - ASPROPYRGOS - GREECE
T: +30 210 55 90 411-2 F: +30 210 55 90 713
email: sales@vemarcoatings.com website: www.vemarcoatings.com

1.4 Emergency telephone number:

Regional Medicines and Poisons Information Centre NI
Pharmacy Department, Royal Hospital Suite
Grosvenor Road Belfast
Telephone: +44 28 90 63 2032
Fax: +44 28 90 24 80 30
Emergency telephone: 844 892 0111
E-mail address: nirdic.nirdic@belfasttrust.hscni.net
Members of the public seeking specific information on poisons should contact:
In England and Wales: NHS 111 - dial 111
In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 1B H360D May damage the unborn child.
Lact. H362 May cause harm to breast-fed children.
STOT RE 2 H373 May cause damage to the nervous system through prolonged or repeated exposure.

Continue on page 2
GB

Trade name: VEMAR COMFORT ANTIFOULING



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

• **Additional information:** The full text of the classification and labelling elements mentioned is given in Section 16.

• **2.2 Label elements**

• **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

• Hazard pictograms



GHS02



GHS05



GHS07



GHS08



GHS09

• Signal word Danger

• Hazard-determining components of labelling:

dicopper oxide

Rosin

pyrithione zinc

Solvent naphtha (petroleum), light arom.

xylene

alkanes, C14-17, chloro

• Hazard statements

H226 Flammable liquid and vapour.

H302+H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H360D May damage the unborn child.

H362 May cause harm to breast-fed children.

H335 May cause respiratory irritation.

H373 May cause damage to the nervous system through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

• Precautionary statements

P263 Avoid contact during pregnancy and while nursing.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P330 Rinse mouth.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Additional information:**

Restricted to professional users.

• **2.3 Other hazards**

• **Results of PBT and vPvB assessment**

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

• PBT:

85535-85-9 alkanes, C14-17, chloro

Trade name: VEMAR COMFORT ANTIFOULING• **vPvB:**

85535-85-9 alkanes, C14-17, chloro

SECTION 3: Composition/information on ingredients• **3.2 Chemical characterisation: Mixtures**• **Description:** Mixture of hazardous substances listed below with nonhazardous additions.• **Dangerous components:**

CAS: 1317-39-1 EINECS: 215-270-7 Index number: 029-002-00-X	dicopper oxide ☠ Eye Dam. 1, H318 ☠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10) ☠ Acute Tox. 4, H302; Acute Tox. 4, H332	30-<45%
CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7	Rosin ☠ Skin Sens. 1, H317	15-<20%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35-0001	Solvent naphtha (petroleum), light arom. ☠ Flam. Liq. 3, H226 ☠ Asp. Tox. 1, H304 ☠ Aquatic Chronic 2, H411 ☠ Acute Tox. 4, H332; STOT SE 3, H335 STOT SE 3, H336 Note: H, P, 4	15-<20%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9	xylene ☠ Flam. Liq. 3, H226 ☠ STOT RE 2, H373; Asp. Tox. 1, H304 ☠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-<15%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 RTECS: ZH 4810000	zinc oxide ☠ Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1)	5-<10%
CAS: 85535-85-9 EINECS: 287-477-0 Index number: 602-095-00-X	alkanes, C14-17, chloro ☠ Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1) Lact., H362 PBT; vPvB	≥2.5-<5%
CAS: 13463-41-7 EINECS: 236-671-3 Index number: 613-333-00-7	pyrithione zinc ☠ Acute Tox. 3, H301; Acute Tox. 2, H330 ☠ Repr. 1B, H360D; STOT RE 1, H372 ☠ Eye Dam. 1, H318 ☠ Aquatic Acute 1, H400 (M=1000); Aquatic Chronic 1, H410 (M=10)	≥1-<2.5%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-0001 01-2119475791-29	2-methoxy-1-methylethyl acetate ☠ Flam. Liq. 3, H226	1-<5%
CAS: 112-07-2 EINECS: 203-933-3 Index number: 607-038-00-2 RTECS: KJ 8925000 Reg.nr.: 01-2119475112-47-0002	2-butoxyethyl acetate ☠ Acute Tox. 4, H312; Acute Tox. 4, H332	1-<5%

• **Additional information:** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures**• **4.1 Description of first aid measures**• **General information:** Immediately remove any clothing soiled by the product.• **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• **After skin contact:** Immediately wash with water and soap and rinse thoroughly.• **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.• **After swallowing:** Call for a doctor immediately.• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.• **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures• **5.1 Extinguishing media**• **Suitable extinguishing agents:** CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Trade name: VEMAR COMFORT ANTIFOULING

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
Firefighters should always wear protective equipment and breathing apparatus when handling fire coming from these products
- **5.6 Fire and explosion Hazards**
- **Special protective equipment and fire fighting procedures:**
Mouth respiratory protective device.
Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.
- **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
• Requirements to be met by storerooms and receptacles: No special requirements.
• Information about storage in one common storage facility: Not required
• Further information about storage conditions: Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
8050-09-7 Rosin
WEL Short-term value: 0.15 mg/m³
Long-term value: 0.05 mg/m³
Sk
1330-20-7 xylene
WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV
108-65-6 2-methoxy-1-methylethyl acetate
WEL Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk
112-07-2 2-butoxyethyl acetate
WEL Short-term value: 332 mg/m³, 50 ppm
Long-term value: 133 mg/m³, 20 ppm
Sk

Trade name: VEMAR COMFORT ANTIFOULING

8050-09-7 Rosin

WEL Short-term value: 0.15 mg/m³
Long-term value: 0.05 mg/m³
Sk

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

112-07-2 2-butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm
Long-term value: 133 mg/m³, 20 ppm
Sk

- Regulatory information WEL: EH40/2020
- DNELs

ATE (Acute Toxicity Estimates)

Inhalative DNELs 3.81 mg/m³

1330-20-7 xylene

Inhalative DNELs 11 mg/m³ (ATE)

112-07-2 2-butoxyethyl acetate

Inhalative DNELs 11 mg/m³ (ATE)

- Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

- Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.

For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Rubber gloves

Continue on page 6
GB

Trade name: VEMAR COMFORT ANTIFOULING

- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical properties

• General Information

• Appearance:

Form:

Fluid

Colour:

According to product specification

• Odour:

Characteristic

• Odour threshold:

Not determined

• pH-value:

Mixture is non-soluble (in water).

• Change in condition

Melting point/freezing point:

Undetermined

Initial boiling point and boiling range:

137 °C (1330-20-7 xylene)

• Flash point:

25 °C

• Flammability

Flammable.

• Autoignition temperature:

450 °C

• Decomposition temperature:

Not determined

• Ignition temperature:

Product is not selfigniting.

• Explosive properties:

Risk of explosion by shock, friction, fire or other sources of ignition.

• Explosion limits:

Lower:

0.7 Vol %

Upper:

7.5 Vol %

• Vapour pressure at 20 °C:

5 hPa

• Density at 20 °C:

1.596 g/cm³

• Relative density

Not determined

• Vapour density

Not determined

• Evaporation rate

Not determined

• Solubility in / Miscibility with

water:

Not miscible or difficult to mix.

• Partition coefficient: n-octanol/water:

Not determined

• Viscosity:

Dynamic:

Not determined

Kinematic at 20 °C:

130.3 mm²/s

Kinematic at 40 °C:

100-110 mm²/s

• Solvent content:

Organic solvents:

28 %

VOC (EC)

446.7-447.5 g/l

Solids content (volume):

72.0 %

• 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

• 10.2 Chemical stability

• **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

• 11.1 Information on toxicological effects

• **Acute toxicity**

Harmful if swallowed or if inhaled.

Trade name: VEMAR COMFORT ANTIFOULING

- LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	1,395 mg/kg
Dermal	LD50	17,753 mg/kg

1317-39-1 dicopper oxide

Oral	LD50	500 mg/kg (ATE)
Inhalative	LC50/4 h	3.34 mg/l (ATE)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

1314-13-2 zinc oxide

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

13463-41-7 pyrrithione zinc

Oral	LD50	221 mg/kg (ATE)
Inhalative	LC50/4 h	0.14 mg/l (ATE)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

112-07-2 2-butoxyethyl acetate

Oral	LD50	2,400 mg/kg (rat)
Dermal	LD50	1,580 mg/kg (rabbit)

- Primary irritant effect:
- Skin corrosion/irritation
Causes skin irritation.
- Serious eye damage/irritation
Causes serious eye damage.
- Respiratory or skin sensitisation
May cause an allergic skin reaction.
- **Additional toxicological information:**
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity
May damage the unborn child.
May cause harm to breast-fed children.
- STOT-single exposure
May cause respiratory irritation.
- STOT-repeated exposure
May cause damage to the nervous system through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea
- **12.2 Persistence and degradability**
This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- Remark: Very toxic for fish
- **Additional ecological information:**
- General notes:
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Very toxic for aquatic organisms

Trade name: VEMAR COMFORT ANTIFOULING

• 12.5 Results of PBT and vPvB assessment

• PBT:

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
85535-85-9 alkanes, C14-17, chloro

• vPvB:

85535-85-9 alkanes, C14-17, chloro

• 12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

• 13.1 Waste treatment methods

• **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• European waste catalogue

HP3 Flammable
HP4 Irritant - skin irritation and eye damage
HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP6 Acute Toxicity
HP10 Toxic for reproduction
HP13 Sensitising
HP14 Ecotoxic

• Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

• 14.1 UN-Number

• ADR, IMDG, IATA

UN1263

• 14.2 UN proper shipping name

• ADR

UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS

• IMDG

PAINT, MARINE POLLUTANT

• IATA

PAINT

• 14.3 Transport hazard class(es)

• ADR



• Class

3 (F1) Flammable liquids.

• Label

3

• IMDG



• Class

3 Flammable liquids.

• Label

3

• IATA



• Class

3 Flammable liquids.

• Label

3

• 14.4 Packing group

• ADR, IMDG, IATA

III

• 14.5 Environmental hazards:

• Marine pollutant:

Product contains environmentally hazardous substances: dicopper oxide, pyrrhione zinc
Symbol (fish and tree)
Symbol (fish and tree)

• Special marking (ADR):

• 14.6 Special precautions for user

Warning: Flammable liquids.

• Hazard identification number (Kemler code):

30

• EMS Number:

F-E,S-E

Trade name: VEMAR COMFORT ANTIFOULING

• <u>Stowage Category</u>	A
• 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable
• Transport/Additional information:	
• <u>ADR</u>	
• <u>Limited quantities (LQ)</u>	5L
• <u>Excepted quantities (EQ)</u>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
• <u>Transport category</u>	3
• <u>Tunnel restriction code</u>	D/E
• <u>IMDG</u>	
• <u>Limited quantities (LQ)</u>	5L
• <u>Excepted quantities (EQ)</u>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
• <u>IATA</u>	
• <u>Remarks:</u>	•3W
• UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- 3Y
- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
None of the ingredients is listed.
- Poisons Act
- Regulated explosives precursors
None of the ingredients is listed.
- Regulated poisons
None of the ingredients is listed.
- Reportable explosives precursors
None of the ingredients is listed.
- Reportable poisons
None of the ingredients is listed.
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



GHS02



GHS05



GHS07



GHS08



GHS09

- Signal word Danger
- Hazard-determining components of labelling:
dicopper oxide
Rosin
pyrithione zinc
Solvent naphtha (petroleum), light arom.
xylene
alkanes, C14-17, chloro
- Hazard statements
H226 Flammable liquid and vapour.
H302+H332 Harmful if swallowed or if inhaled.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H360D May damage the unborn child.
H362 May cause harm to breast-fed children.
H335 May cause respiratory irritation.
H373 May cause damage to the nervous system through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.
- Precautionary statements
P263 Avoid contact during pregnancy and while nursing.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Trade name: VEMAR COMFORT ANTIFOULING

- P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P330 Rinse mouth.
P362+P364 Take off contaminated clothing and wash it before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Directive 2012/18/EU**
 - **Named dangerous substances - ANNEX I** None of the ingredients is listed.
 - **Seveso category**
E1 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t
 - **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 30
 - **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**
None of the ingredients is listed.
 - **REGULATION (EU) 2019/1148**
 - **Annex I - RESTRICTED EXPLOSIVES PRECURSORS** (Upper limit value for the purpose of licensing under Article 5(3))
None of the ingredients is listed.
 - **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**
None of the ingredients is listed.
 - **Regulation (EC) No 273/2004 on drug precursors**
None of the ingredients is listed.
 - **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**
None of the ingredients is listed.
 - **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H226 Flammable liquid and vapour.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H360D May damage the unborn child.
H362 May cause harm to breast-fed children.
H372 Causes damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

• Classification according to Regulation (EC) No 1272/2008

Flammable liquids
Acute toxicity - oral
Acute toxicity - inhalation
Skin corrosion/irritation
Serious eye damage/irritation
Skin sensitisation
Reproductive toxicity
Specific target organ toxicity (single exposure)
Specific target organ toxicity (repeated exposure)
Hazardous to the aquatic environment - short-term (acute) aquatic hazard
Hazardous to the aquatic environment - long-term (chronic) aquatic hazard

Bridging principles

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Trade name: VEMAR COMFORT ANTIFOULING

· **Contact:**



VEMAR YACHT COATINGS
HB BODY S.A. ATHENS - DIYLISTIRION AV. - GR 19300 - ASPROPYRGOS - GREECE
T: +30 210 55 90 411-2 F: +30 210 55 90 713
email: sales@vemarcoatings.com website: www.vemarcoatings.com

· *** Data compared to the previous version altered.**

GB
Continue on page 12

Trade name: VEMAR COMFORT ANTIFOULING

Annex: Exposure scenario

- **Short title of the exposure scenario**
- **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC8 Biocidal products
- **Process category** PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
- **Article category** AC30 Other articles with intended release of substances
- **Environmental release category** ERC12c Use of articles at industrial sites with low release
- **Technical function** Biocide
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use** According to directions for use.
- **Duration and frequency** Frequency of use:
- **Physical parameters**
The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.
- **Physical state** Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Used amount per time or activity** Smaller than 100 g per application.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** Use only on hard ground.
- **Other operational conditions affecting worker exposure**
Avoid contact with eyes.
Avoid contact with the skin.
Avoid long-term or repeated skin contact.
Do not breathe gas/vapour/aerosol.
Take precautionary measures against static discharge.
Keep away from sources of ignition - No smoking.
- **Other operational conditions affecting consumer exposure** No special measures required.
- **Other operational conditions affecting consumer exposure during the use of the product** Not applicable
- **Risk management measures**
- **Worker protection**
- Organisational protective measures
Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.
- Technical protective measures
Provide explosion-proof electrical equipment.
Use product only in enclosed systems.
Ensure that suitable extractors are available on processing machines
- Personal protective measures
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes.
Pregnant women should strictly avoid inhalation or skin contact.
Tightly sealed goggles
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Measures for consumer protection**
Ensure adequate labelling.
Observe consumer information and advice on safe use.
- **Environmental protection measures**
- Water
Generally, prior to the introduction of wastewater into wastewater treatment plants a neutralisation is required.
Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.
Do not allow to reach sewage system.
- Soil
Prevent contamination of soil.
The product is only processed over the concrete collecting basin.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer**
Not relevant for this Exposure Scenario.
This product is to be used by professional technicians only.
- **Guidance for downstream users**
Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.