

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name: **VEMAR HI SPEED PLUS ANTIFOULING**

Article number: 644

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

- Life cycle stages PW Widespread use by professional workers
- Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- Product category PC8 Biocidal products
- Process category PROC7 Industrial spraying
- Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article
- Article category AC7 Metal articles
- Application of the substance / the mixture  
 Antifouling paint  
 Surface protection

**1.3 Details of the supplier of the safety data sheet**

**Manufacturer/Supplier:**



VEMAR YACHT COATINGS  
 HB BODY S.A. ATHENS - DIYLISTIRION AV. - GR 19300 - ASPROPYRGOS - GREECE  
 T: +30 210 55 90 411-2 F: +30 210 55 90 713  
 email: sales@vemarcoatings.com website: www.vemarcoatings.com

**Further information obtainable from:**



VEMAR YACHT COATINGS  
 HB BODY S.A. ATHENS - DIYLISTIRION AV. - GR 19300 - ASPROPYRGOS - GREECE  
 T: +30 210 55 90 411-2 F: +30 210 55 90 713  
 email: sales@vemarcoatings.com website: www.vemarcoatings.com

**1.4 Emergency telephone number:**

Regional Medicines and Poisons Information Centre NI  
 Pharmacy Department, Royal Hospital Suite  
 Grosvenor Road Belfast  
 Telephone: +44 28 90 63 2032  
 Fax: +44 28 90 24 80 30  
 Emergency telephone: 844 892 0111  
 E-mail address: nirdic.nirdic@belfasttrust.hscni.net

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.

Trade name: **VEMAR HI SPEED PLUS ANTIFOULING**

(Contd. of page 1)



GHS09 environment

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

• **2.2 Label elements**

• **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.

• Hazard pictograms



GHS02



GHS05



GHS07



GHS09

• Signal word Danger

• Hazard-determining components of labelling:

Pyrithione zinc

Solvent naphtha (petroleum), light arom.

Rosin

xylene

5-[1-(2,3-dimethylphenyl)ethyl]-1H-imidazole

• Hazard statements

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

• Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P330 Rinse mouth.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **2.3 Other hazards**

• **Results of PBT and vPvB assessment**

• PBT: Not applicable.

• vPvB: Not applicable.

\* **SECTION 3: Composition/information on ingredients**

• **3.2 Chemical characterisation: Mixtures**

• **Description:** Mixture of hazardous substances

(Contd. on page 3)

GB

## Trade name: VEMAR HI SPEED PLUS ANTIFOULING

(Contd. of page 2)

### · Dangerous components:

CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35-0001	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Acute Tox. 4, H332; STOT SE 3, H335-H336	20-<25%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 RTECS: ZH 4810000	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	15-<20%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9	xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	5-<10%
CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7	Rosin Skin Sens. 1, H317	5-<10%
CAS: 13463-41-7 EINECS: 236-671-3	Pyrrithione zinc Consisting of: 13463-41-7 Pyrrithione zinc (100%) Acute Tox. 3, H301; Acute Tox. 3, H331 Eye Dam. 1, H318 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥3-<5%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-0001 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	<2.5%
CAS: 112-07-2 EINECS: 203-933-3 Index number: 607-038-00-2 RTECS: KJ 8925000 Reg.nr.: 01-2119475112-47-0002	2-butoxyethyl acetate Acute Tox. 4, H312; Acute Tox. 4, H332	<2.5%
CAS: 86347-14-0 Index number: 613-321-00-1	5-[1-(2,3-dimethylphenyl)ethyl]-1H-imidazole Acute Tox. 2, H300; Acute Tox. 2, H330 STOT SE 1, H370; STOT RE 1, H372 Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=100) STOT SE 3, H336	≥0.025-<0.25%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### · 4.1 Description of first aid measures

#### · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Call for a doctor immediately.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

## SECTION 5: Firefighting measures

### · 5.1 Extinguishing media

· **Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

## Trade name: VEMAR HI SPEED PLUS ANTIFOULING

(Contd. of page 3)

### • 5.3 Advice for firefighters

Firefighters should always wear protective equipment and breathing apparatus when handling fire coming from these products

### • Special protective equipment and fire fighting procedures:

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

• **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

## SECTION 6: Accidental release measures

### • 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

### • 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

### • 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

### • 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

### • 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

### • Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

### • 7.2 Conditions for safe storage, including any incompatibilities

#### • Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

• Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Keep container tightly sealed.

• **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

• **Additional information about design of technical facilities:** No further data; see item 7.

### • 8.1 Control parameters

• **Ingredients with limit values that require monitoring at the workplace:**

#### 1330-20-7 xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm

Long-term value: 220 mg/m<sup>3</sup>, 50 ppm

Sk; BMGV

#### 8050-09-7 Rosin

WEL Short-term value: 0.15 mg/m<sup>3</sup>

Long-term value: 0.05 mg/m<sup>3</sup>

Sen

#### 108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm

Long-term value: 274 mg/m<sup>3</sup>, 50 ppm

Sk

#### 112-07-2 2-butoxyethyl acetate

WEL Short-term value: 332 mg/m<sup>3</sup>, 50 ppm

Long-term value: 133 mg/m<sup>3</sup>, 20 ppm

Sk

(Contd. on page 5)

## Trade name: VEMAR HI SPEED PLUS ANTIFOULING

(Contd. of page 4)

- Regulatory information WEL: EH40/2018
- Ingredients with biological limit values:  
**1330-20-7 xylene**  
BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid
- Additional information: The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- General protective and hygienic measures:  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.
- Respiratory protection:  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Protection of hands:



Protective gloves

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
  - Penetration time of glove material  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
  - For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:  
The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.
  - For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
  - For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Rubber gloves
  - Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- Appearance:  
Form: Fluid  
Colour: According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- **pH-value:** Not determined.
- **Change in condition**  
Melting point/freezing point: Undetermined.  
Initial boiling point and boiling range: 140 °C
- **Flash point:** 23 - 60 °C

(Contd. on page 6)

## Trade name: VEMAR HI SPEED PLUS ANTIFOULING

(Contd. of page 5)

- **Flammability (solid, gas):** Not applicable.
- **Autoignition temperature:** 450 °C
- **Decomposition temperature:** Not determined.
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Risk of explosion by shock, friction, fire or other sources of ignition.
- **Explosion limits:**
  - Lower: 0.7 Vol %
  - Upper: 7.5 Vol %
- **Vapour pressure at 20 °C:** 5 hPa
- **Density at 20 °C:** 1.438 g/cm<sup>3</sup>
- Relative density: Not determined.
- Vapour density: Not determined.
- Evaporation rate: Not determined.
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
  - Dynamic: Not determined.
  - Kinematic at 40 °C: 80-90 mm<sup>2</sup>/s
- **Solvent content:**
  - Organic solvents: 34.6 %
  - VOC (EC) 497.5 g/l
  - Solids content (volume): 43.8 %
- **9.2 Other information** No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Harmful if swallowed.

##### LD/LC50 values relevant for classification:

##### ATE (Acute Toxicity Estimates)

Oral LD50 2,315 mg/kg

Dermal LD50 20,983 mg/kg

Inhalative LC50/4 h 11.5 mg/l

##### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6,800 mg/kg (rat)

Dermal LD50 >3,400 mg/kg (rab)

Inhalative LC50/4 h >10.2 mg/l (rat)

##### 1314-13-2 zinc oxide

Oral LD50 >5,000 mg/kg (rat)

##### 13463-67-7 titanium dioxide

Oral LD50 >20,000 mg/kg (rat)

Dermal LD50 >10,000 mg/kg (rabbit)

(Contd. on page 7)

GB

Trade name: **VEMAR HI SPEED PLUS ANTIFOULING**

(Contd. of page 6)

Inhalative LC50/4 h >6.82 mg/l (rat)

**1330-20-7 xylene**

Oral LD50 4,300 mg/kg (rat)  
Dermal LD50 2,000 mg/kg (rabbit)  
Inhalative LC50/4 h 11 mg/l (ATE)

**13463-41-7 Pyrithione zinc**

Oral LD50 100 mg/kg (ATE)  
Inhalative LC50/4 h 0.5 mg/l (ATE)

**108-65-6 2-methoxy-1-methylethyl acetate**

Oral LD50 8,532 mg/kg (rat)  
Inhalative LC50/4 h 35.7 mg/l (rat)

**112-07-2 2-butoxyethyl acetate**

Oral LD50 2,400 mg/kg (rat)  
Dermal LD50 1,580 mg/kg (rabbit)  
Inhalative LC50/4 h 11 mg/l (ATE)

**86347-14-0 5-[1-(2,3-dimethylphenyl)ethyl]-1H-imidazole**

Oral LD50 31.25 mg/kg (rat)  
31.25 mg/kg (rabbit)  
Dermal LD50 >2,000 mg/kg (rat)  
Inhalative LC50/4 h 0.14 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation  
Causes serious eye damage.
- Respiratory or skin sensitisation  
May cause an allergic skin reaction.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure  
May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

\* **SECTION 12: Ecological information**

• **12.1 Toxicity**

• **Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

**86347-14-0 5-[1-(2,3-dimethylphenyl)ethyl]-1H-imidazole**

EC50 4.5 mg/kg (daphnia)

• **12.2 Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

• **12.3 Bioaccumulative potential** No further relevant information available.

• **12.4 Mobility in soil** No further relevant information available.

• **Additional ecological information:**

• General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Must not reach sewage water or drainage ditch undiluted or unneutralised.  
Danger to drinking water if even extremely small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.

• **12.5 Results of PBT and vPvB assessment**

- **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- **vPvB:** Not applicable.

(Contd. on page 8)

Trade name: **VEMAR HI SPEED PLUS ANTIFOULING**






(Contd. of page 7)

- **12.6 Other adverse effects** No further relevant information available.

\* **SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**
  - HP3 Flammable
  - HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
  - HP14 Ecotoxic
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

\* **SECTION 14: Transport information**

- **14.1 UN-Number**
  - **ADR, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
  - **ADR** UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS
  - **IMDG** PAINT (Solvent naphtha (petroleum), light arom., zinc oxide), MARINE POLLUTANT
  - **IATA** PAINT
- **14.3 Transport hazard class(es)**
  - **ADR**
    -  
    - **Class** 3 (F1) Flammable liquids.
    - **Label** 3
  - **IMDG**
    -  
    - **Class** 3 Flammable liquids.
    - **Label** 3
  - **IATA**
    - 
    - **Class** 3 Flammable liquids.
    - **Label** 3
- **14.4 Packing group**
  - **ADR, IMDG, IATA** III
- **14.5 Environmental hazards:**
  - **Marine pollutant:** Product contains environmentally hazardous substances: Pyrithione zinc
  - **Special marking (ADR):** Symbol (fish and tree)
- **14.6 Special precautions for user**
  - **Danger code (Kemler):** Warning: Flammable liquids.
  - **EMS Number:** 30
  - **Stowage Category:** F-E, S-E
- **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**
  - **Stowage Category:** A
  - **IBC Code:** Not applicable.

(Contd. on page 9)



Trade name: **VEMAR HI SPEED PLUS ANTIFOULING**

(Contd. of page 8)

• **Transport/Additional information:**

- ADR
- Limited quantities (LQ)
- Excepted quantities (EQ)

5L  
Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml  
3  
D/E

- Transport category
- Tunnel restriction code
- IMDG
- Limited quantities (LQ)
- Excepted quantities (EQ)

5L  
Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

• **UN "Model Regulation":**

UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

**SECTION 15: Regulatory information**

•3Y

• **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

• **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.

• Hazard pictograms



GHS02 GHS05 GHS07 GHS09

• Signal word Danger

• Hazard-determining components of labelling:

Pyrithione zinc

Solvent naphtha (petroleum), light arom.

Rosin

xylene

5-[1-(2,3-dimethylphenyl)ethyl]-1H-imidazole

• Hazard statements

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

• Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P330 Rinse mouth.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Directive 2012/18/EU**

• Named dangerous substances - ANNEX I None of the ingredients is listed.

• Seveso category

E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 10)

GB

## Trade name: VEMAR HI SPEED PLUS ANTIFOULING

(Contd. of page 9)

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

### SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
  - H226 Flammable liquid and vapour.
  - H300 Fatal if swallowed.
  - H301 Toxic if swallowed.
  - H304 May be fatal if swallowed and enters airways.
  - H312 Harmful in contact with skin.
  - H315 Causes skin irritation.
  - H317 May cause an allergic skin reaction.
  - H318 Causes serious eye damage.
  - H319 Causes serious eye irritation.
  - H330 Fatal if inhaled.
  - H331 Toxic if inhaled.
  - H332 Harmful if inhaled.
  - H335 May cause respiratory irritation.
  - H336 May cause drowsiness or dizziness.
  - H370 Causes damage to organs.
  - H372 Causes damage to organs through prolonged or repeated exposure.
  - H373 May cause damage to organs through prolonged or repeated exposure.
  - H400 Very toxic to aquatic life.
  - H410 Very toxic to aquatic life with long lasting effects.
  - H411 Toxic to aquatic life with long lasting effects.
  - H412 Harmful to aquatic life with long lasting effects.

- **Contact:**



VEMAR YACHT COATINGS  
HB BODY S.A. ATHENS - DIYLITIRION AV. - GR 19300 - ASPROPYRGOS - GREECE  
T: +30 210 55 90 411-2 F: +30 210 55 90 713  
email: sales@vemarcoatings.com website: www.vemarcoatings.com

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 3: Flammable liquids – Category 3  
Acute Tox. 2: Acute toxicity – Category 2  
Acute Tox. 3: Acute toxicity – Category 3  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Skin Sens. 1: Skin sensitisation – Category 1  
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- \* **Data compared to the previous version altered.**

GB  
(Contd. on page 11)

**Trade name: VEMAR HI SPEED PLUS ANTIFOULING**

(Contd. of page 10)

**Annex: Exposure scenario**

- **Short title of the exposure scenario**
- **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC8 Biocidal products
- **Process category** PROC7 Industrial spraying
- **Article category** AC7 Metal articles
- **Environmental release category** ERC5 Use at industrial site leading to inclusion into/onto article
- **Description of the activities / processes covered in the Exposure Scenario**  
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use** According to directions for use.
- **Duration and frequency** Frequency of use:
- **Physical parameters**  
The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.
- **Physical state** Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** Use only on hard ground.
- **Other operational conditions affecting worker exposure**  
Avoid contact with the skin.  
Do not breathe gas/vapour/aerosol.  
Take precautionary measures against static discharge.  
Keep away from sources of ignition - No smoking.  
Avoid contact with eyes.  
Avoid long-term or repeated skin contact.
- **Other operational conditions affecting consumer exposure** No special measures required.
- **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.
- **Risk management measures**
- **Worker protection**
- Organisational protective measures  
Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.
- Technical protective measures  
Provide explosion-proof electrical equipment.  
Use product only in enclosed systems.  
Ensure that suitable extractors are available on processing machines
- Personal protective measures  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the skin.  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.  
Protective gloves  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  
Avoid contact with the eyes.  
Tightly sealed goggles
- **Measures for consumer protection**  
Ensure adequate labelling.  
Observe consumer information and advice on safe use.
- **Environmental protection measures**
- Water  
Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.  
Do not allow to reach sewage system.  
Generally, prior to the introduction of wastewater into wastewater treatment plants a neutralisation is required.
- Soil  
Prevent contamination of soil.  
The product is only processed over the concrete collecting basin.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** This product is to be used by professional technicians only.
- **Guidance for downstream users**  
Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.