PRODUCT DATA SHEET

Teak Defender Sealer



Description

A water-based wood protection solution for exterior bare wood. Free from oils or petroleum residues. Contains active substances, that protect the cellulose structure of the wood from degradation and prevents the discoloration of wood caused by excessive sunlight exposure.

Suggested uses

- On all kinds of exterior bare solid wood, teak and plywood, as a sealing layer that steadily reduces the oxidation and discoloration rate.
- As the step 3 of the Teak Defender series, following the application of Teak Defender cleaner (step 1) and Teak Defender Brightener (step 2).

Product details

Available shades: Transparent Orange Specific gravity: $1,00 \pm 0,05 \text{ g/ml}$

Shelf life (20°C): 2 years

Theoretical spreading

rate: 6 m²/L

VOC (as supplied) according to

ISO 11890-2:2013: 53 g/L

Packaging: 0,75 L, 2,5 L

Surface preparation

Apply Teak Defender Cleaner and Teak Defender Brightener according to the instructions as stated in the relevant product's data sheets or sand the surface.

Application guidelines

Apply 1-2 coats with brush and allow to penetrate for 20 minutes. Excess material can be wiped off.

Tool cleaning

After use, clean equipment thoroughly with Water.

Storage

Store in a cool and shaded area in temperatures $+5^{\circ}$ C up to $+25^{\circ}$ C. Storage in temperatures higher than indicated will reduce the shelf life of the product.

Health, safety & protection

Always use appropriate safety equipment for your face, eyes and skin. Make sure that the area where the product is being used is well ventilated. ALWAYS CONSULT THE MATERIAL SAFETY DATA SHEET BEFORE USE. Do not pour the containment or any remains in an aqueous environment or drainage. Do not dispose remains in municipal waste areas. Consult your local authorities for the disposal of any remains or empty cans.

Disclaimer

The information, data, guidance and any recommendations provided herein are based on Vemar's know-how, laboratory testing and obtained experience and is correct to the best of our knowledge. Users should contact their closest Vemar representative in order to receive guidance according to their special application needs not referred in this document. The performance of the product under the actual conditions of any intended use where Vemar will not have access to the various conditions affecting the use and application of the product, is not guaranteed and must be determined by the user. This document may be altered any time in the context of Vemar's continuous improvement and development. The supplied products and all technical assistance will be under the General condition of sales & delivery. By using this product as recommended in this document it is stated that the manufacturer and or seller, and the buyer and or user waives all claims involving, any liability, included but not limited to negligence, injury or direct or consequential losses or damages.

PAGE 1 OF 1 ISSUE DATE / 21.12.2020